

For more on material solutions for off road vehicles, visit avient.com



Copyright © 2020, Avient Corporation. Avient makes no representations, guarantees, or warranties of any kind with respect to the information contained in this document about its accuracy, suitability for particular applications, or the results obtained or obtainable using the information. Some of the information arises from laboratory work with small-scale equi not provide a reliable indication of performance or properties obtained or obtainable on larger-scale equipment. Values reported as "typical" or stated without a range do not state minimum or maximum properties; consult your sales representative for property ranges and min/max specifications. Processing conditions can cause material properties to shift from the values stated in the information. Avient makes no warranties or guarantees respecting suitability of either Avient's products or the information for your process or end-use application, and you assume all risk and liability arising from your use of the information and/or use or handling of any product. AVIENT MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, either with respect to the information or products reflected by the information. This literature shall NOT operate as permission, recommendation, or inducement to practice any patented invention without permission of the patent owner

High Stiffness-to-Weight Ratio,

**SOLUTION:** Pultruded Rods,

Tubes & Custom Profiles, Long

**Fiber Reinforced Composites** 

Metal Replacement

**Composite Tapes & Laminates** 

Lightweighting, Heat Management, Load Carrying Capability

**SOLUTION:** Long Fiber Reinforced Composites, Continuous Fiber

METAL REPLACEMENT

**Composite Tapes & Laminates**