


DUPONT™ ZYTEL® HTN HIGH PERFORMANCE POLYAMIDE RESIN PRODUCT REFERENCE GUIDE

DuPont™ Zytel® HTN cost effectively bridges the performance gap between conventional engineering resins and high-end specialty polymers. Zytel® HTN PPA grades retain stiffness, strength and mechanical properties despite exposure to high temperatures, chemicals and moisture, making them ideal for automotive underhood components and systems, as well as electrical and electronic connectors and bushings. Structural grades of Zytel® HTN help provide larger display areas when used in backbones for cell phones, tablets and other hand-held devices. Talk to DuPont about how Zytel® HTN can deliver a solution to your unique challenges.



Based on semi-aromatic structure, Zytel® HTN offers a balance of chemical, moisture and temperature resistance, plus outstanding processability.

DUPONT™ ZYTEL® HTN PRODUCT SELECTION

Product portfolio is ranked generically by increasing property retention in the specific end-use environment. Product ranking is determined by the typical best performance for the specific application requirement.

← Increasing Property Retention

Temperature	HTN51	HTN55	HTN52	HTN54	HTN53	HTN59
Moisture	HTN51	HTN54	HTN53*	HTN55	HTN52	HTN59
Chemicals	HTN51	HTN54	HTN52	HTN59	HTN55	HTN53
Heat-aging	HTN51	HTN54	HTN52	HTN55	HTN53	HTN59



← Increasing Performance

Creep	HTN51	HTN52	HTN55	HTN54	HTN53	HTN59
Toughness	HTN53	HTN59	HTN54	HTN51	HTN55	HTN52
Dimensions (w.moisture)	HTN59	HTN51	HTN54	HTN52	HTN55	HTN53
Surface Aesthetics	HTN59	HTN53	HTN51	HTN55	HTN52	HTN54

* HTN53 property retention in moist environments dependent on temperature range. These are general guidelines and product selection is typically dependent upon multiple factors.

DUPONT™ ZYTEL® HTN PPA RESINS

Performance Comparison



Applications

- **Zytel® HTN51:** Water thermal management, auto E/E, electrical components
- **Zytel® HTN52:** Electronic connectors, electrical components
- **Zytel® HTN54:** Auto E/E, fuel connectors
- **Zytel® HTN55:** Handheld devices - laptop covers
- **Zytel® HTN92:** Hot air thermal management

DUPONT™ ZYTEL® HTN STRUCTURAL RESINS

Applications


- Zytel® HTN53: Furniture, cell phones
- Zytel® RS HTN59: Cell phones

DUPONT™ ZYTEL® HTN RESINS IN HANDHELD DEVICES

With excellent flow, dimensional stability, toughness and strength, Zytel® HTN can reduce the total system cost of thinner and lighter housings for laptop computers, tablet PCs, cell phones and other devices.



Performance Comparison



Polyamides contain 50-55% GF reinforcement

DUPONT™ ZYTEL® HTN GLOBAL PRODUCT PORTFOLIO

	Zytel® HTN51		Zytel® HTN52	Zytel® HTN53	Zytel® HTN54	Zytel® HTN55
Glass Reinforced	51G15HSL 51G35EF 51G35HSL	51G35HSLR 51G35FWS 51G45HSL	52G35EF 52G35HSL 52G45HSL	53G35LRHF 53G50HSLR 53G60LRHF	54G15HSLR 54G35EF 54G35HSLR	55G55TLW
Ultra High Stiffness				53C40HSL		
Low Warp						55G55TLW FR55G50NHLW
Flame Retardant			FR52G20NH FR52G30BL FR52G30 NH FR52G35NHF FR52G43HF			FR55G50NHLW FR55G55NHLW
Toughened/ Unreinforced	FE8200					
Static Dissipative				53C40HSL	FE350064	
Food Contact	FG52G35HSL					

Many other grades are available by region. Please connect with DuPont for your specialized needs.

Visit us at plastics.dupont.com or zytelhtn.dupont.com

Contact DuPont at the following regional locations:

North America
+1-302-999-4592

Latin America
+0800 17 17 15

Europe, Middle East, Africa
+41 22 717 51 11

Greater China
+86-400-8851-888

Japan
+81-3-5521-8600

ASEAN
+65 6586 3688

The information provided in this guide corresponds to DuPont knowledge on the subject at the date of its publication. This information may be subject to revision as new knowledge and experience becomes available. The data provided fall within the normal range of product properties and relate only to the specific material designated; these data may not be valid for such material used in combination with any other materials, additives or pigments or in any process, unless expressly indicated otherwise.

The data provided should not be used to establish specification limits or used alone as the basis of design; they are not intended to substitute for any testing you may need to conduct to determine for yourself the suitability of a specific material for your particular purposes. Since DuPont cannot anticipate all variations in actual end-use and disposal conditions, DuPont does not guarantee results, makes no warranties and assumes no liability in connection with any use of this information. All such information is given and accepted at the buyer's risk. It is intended for use by persons having technical skill, at their own discretion and risk. Nothing in this publication is to be considered as a license to operate under or a recommendation to infringe any patent.

CAUTION: Do not use DuPont materials in medical applications involving implantation in the human body or contact with internal body fluids or tissues unless the material has been provided from DuPont under a written contract that is consistent with DuPont policy regarding medical applications and expressly acknowledges the contemplated use. For further information, please contact your DuPont representative. You may also request a copy of DuPont POLICY Regarding Medical Applications H-50103-5 and DuPont CAUTION Regarding Medical Applications H-50102-5. Copyright ©2016 DuPont. The DuPont Oval Logo, DuPont™ and Zytel® are trademarks or registered trademarks of E.I. du Pont de Nemours and Company or its affiliates. All rights reserved. (06/16) Reference number GNE-A11211-00-A0516

