



GEON® A-Series Industrial Tubing Formulations

GEON A-Series formulations for industrial tubing are available to suit a wide range of applications and performance requirements. With varying levels of hardness and tensile strength achievable, as well as custom color matching, hose and tubing can be easily customized to meet both functional and aesthetic needs.

In addition to supplying formulations matched to end-use applications, a GEON support team can help navigate through material regulations to ensure compliance and mitigate risk. An extrusion technical support team, specifically covering North America, is also available to assist with production issues and operating efficiencies, helping to manage costs and save time.

KEY CHARACTERISTICS

- CPSIA and Proposition 65 compliant
- Wide range of durometers
- Custom colors available
- Custom stocking plans available
- NSF and FDA grades and regulatory support available
- Paired with GEON rigid PVC formulations for rugged spiral reinforcement

MARKETS AND APPLICATIONS

- Pool and spa tubing
- Pneumatic tubing
- Industrial hose
- Food, beverage and dairy handling





DUROMETER	TENSILE STRENGTH	CA PROP 65	NSF 61	3-A	PRODUCT
ASTM D-2240 (15s delay)	ASTM D-638 (psi)				
72A	2000	•			A75065X
		•	•		A75065FN
		•	•	•	A75065FND
75A	2200	•			A80065X
		•	•		A80065N
		•	•	•	A80065FND
78A	2450	•			A88065X
		•	•		A88065FN
		•	•	•	A88065FND

1-888-910-0536
WWW.GEON.COM



Copyright © 2019, GEON Performance Solutions. GEON Performance Solutions makes no representations, guarantees, or warranties of any kind with respect to the information contained in this document about its accuracy, suitability for particular applications, or the results obtained or obtainable using the information. Some of the information arises from laboratory work with small-scale equipment which may not provide a reliable indication of performance or properties obtained or obtainable on larger-scale equipment. Values reported as "typical" or stated without a range do not state minimum or maximum properties; consult your sales representative for property ranges and min/max specifications. Processing conditions can cause material properties to shift from the values stated in the information. GEON makes no warranties or guarantees respecting suitability of either GEON's products or the information for your process or end-use application. You have the responsibility to conduct full-scale end-product performance testing to determine suitability in your application, and you assume all risk and liability arising from your use of the information and/or use or handling of any product. GEON MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, either with respect to the information or products reflected by the information. This literature shall NOT operate as permission, recommendation, or inducement to practice any patented invention without permission of the patent owner.